

Le terre cotte dell'Umbria

Realizzata con la più avanzata tecnologia del gres porcellanato, frutto di un grande sforzo di ricerca e di cura nell'esecuzione, Terre Cotte dell'Umbria esprime l'individualità preziosa della lavorazione artigiana e la nitida memoria delle antiche pietre e terrecotte umbre; l'inafferrabilità dei colori, la patinatura della superficie ed i bordi sapientemente consumati raccontano di una storia "antica" che rivive nel presente.

Manufactured with the most advanced technology of glazed porcelain, result of a great research effort and care in execution, Terre Cotte dell'Umbria expresses the precious individuality of handwork and the sharp memory of ancient stones and Umbrian terracotte. The elusive colours, the coating of the surface and the edges worn out with ability tell us about an "ancient" history that revives in the present.

Spoletto



Assisi




Orvieto



Gubbio



Giano



MADE
IN
TAGINA





/ Assisi 30,5x30,5 Fondo - 15x30,5 Fondo - 15x15 Fondo
7,6x30,5 Listello - 7,6x7,6 Tozzetto



/ Gubbio 30,5x30,5 Fondo - 10x35 Battiscopa





/ Orvieto 30,5x30,5 Fondo - 15x30,5 Fondo



/ Giano 30,5x30,5 Fondo - 10x35 Battiscopa

Giano

> colori - Assisi **90** Orvieto **92**
 Spoleto **91** Gubbio **96**
 Giano **97**

> fondo
 41 x 41cm - 16¹¹/₈ x 16¹¹/₈
96F00/P**



> listello
 7,6 x 41cm - 2¹⁵/₁₆ x 16¹¹/₈
96DLS/P**



> fondo
 30,5 x 30,5cm - 12" x 12"
96F30/P**



> fondo
 15 x 30,5cm - 5⁷/₈ x 12"
96F13/P**



> fondo
 15 x 15cm - 5⁷/₈ x 5⁷/₈
96F15/P**



> Listello
 7,6 x 30,5cm - 2¹⁵/₁₆ x 12"
96D73/P**



> Tozzetto
 7,6 x 7,6cm - 2¹⁵/₁₆ x 2¹⁵/₁₆
96DTZ/P**



> Battiscopa
 10 x 35cm - 3¹⁵/₁₆ x 13³/₄
96DBA/P**



> Battiscopa Guscio dx
 10 x 35cm - 3¹⁵/₁₆ x 13³/₄
96DDB/P**



> Battiscopa Guscio sx
 10 x 35cm - 3¹⁵/₁₆ x 13³/₄
96DSB/P**



> Elemento a "Elle" monolitico
 16 x 30,5 x 4cm - 6¹⁵/₁₆ x 12" x 1⁹/₁₆
96D90EL1 Assisi
96D97EL1 Giano



> Gradone
 30,5 x 33,3cm - 12" x 13"
96DGN/P**



> Angolo Gradone Dx-Sx
 30,5 x 33,3cm - 12" x 13"
96DDX/P - 96D**SX/P**





/ Spoleto 30,5x30,5 Fondo - 15x30,5 Fondo - 15x15 Fondo
7,6x30,5 Listello - 7,6x7,6 Tozzetto

packing list / IMBALLAGGI - PACKING - VERPACKUNG - EMBALLAGE - УПАКОВОЧНЫЙ СПИСОК - 包装

Gres Porcellanato ad alto spessore 12 mm
 Porcelain tiles 12 mm thickness
 Feinsteinzeug mit einer Stärke von 12 mm
 Grès cèrame de forte épaisseur 12 mm
 Керамогранит с высокой толщиной 12 мм
 12 mm加厚瓷砖

Formato Size Format Format Размер 规格	Denominazione Description Bezeichnung Description Наименование 名称	Spessore Thickness Stärke Epaisseur Толщина 厚度	PZ / PAC PCS / PACK STK / KAR PCS / PAQUET ШТ. / КОРОБКА 片/包	MQ / PAC SQM / PACK QM / KAR M ² / PAQUET M ² / УПАКОВКА 平方米/包	KG / PAC KG / PACK KG / KAR KG / PAQUET KG / УПАКОВКА 公斤/包	PAC / PAL PACK / PAL KAR / PAL PAQ / PAL КОРОБКА / ПАЛЛЕТ 包/PAL	MQ / PAL SQM / PAL QM / PAL M ² / PAL M ² / ПАЛЛЕТА 平方米/PAL	KG / PAL KG / PAL KG / PAL KG / PAL KG / ПАЛЛЕТА 公斤/PAL
41 x 41 - 16 ^{11/8} x 16 ^{11/8}	Fondo	12	7	1,1767	30,60	48	56,48	1500
30,5 x 30,5 - 12" x 12"	Fondo	12	12	1,1163	28,75	40	44,65	1175
15 x 30,5 - 5 ^{7/8} x 12"	Fondo	12	22	1,0100	23,75	44	44,44	1065
15 x 15 - 5 ^{7/8} x 5 ^{7/8}	Fondo	12	24	0,5400	13,80	80	43,20	1130
7,6 x 30,5 - 2 ^{15/16} x 12"	Listello	12	34	0,7881	19,00	-	-	-
7,6 x 41 - 2 ^{15/16} x 16 ^{11/8}	Listello	12	34	1,0600	25,50	-	-	-
7,6 x 7,6 - 2 ^{15/16} x 2 ^{15/16}	Tozzetto	12	84	0,4872	11,50	-	-	-
30,5 x 33,3 - 12" x 13"	Gradone / Gradone Angolo	35	4	0,4068	25,70	34	13,83	905
10 x 35 - 3 ^{15/16} x 13 ^{3/4}	Battiscopa / Battiscopa Guscio	12	32	11,20m/lin	26,00	42	470,40m/lin	1092
16 x 30,5 x 4 - 6 ^{5/16} x 12" x 1 ^{9/16}	Elemento a "Elle"	12	8	2,44m/lin	14,30	34	82,96m/lin	510

Per comprensibili motivi tecnici i pesi sopra indicati possono variare +/- del 4%.

The above mentioned weights may change for technical reasons for +/- 4%.

Pour des motifs techniques les poids au-dessus mentionnés peuvent changer de +/- 4%.

Die oben angegebenen Gewichte können sich aus technischen Gründen um +/- 4% ändern.

По понятным техническим причинам выше указанная нагрузка веса может изменяться от + 4% до - 4%.

由于技术原因，权重可能会有所差别，正负可相差4%左右

caratteristiche tecniche /

TECHNICAL CHARACTERISTICS - CARACTÉRISTIQUES TECHNIQUES - TECHNISCHE KENNZEICHEN - ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ - 技术属性



GL-UGL	GL-UGL	GL-UGL	GL	GL-UGL
Spessore	Assorbimento acqua	Resistenza al gelo	Resistenza abrasione	Durezza superficiale
Thickness	Water absorption	Frost resistance	Abrasion resistance	Scratch resistance
Epaisseur	Absorption d'eau	Résistance au gel	Résistance à l'abrasion	Dureté superficielle
Stärke	Wasseraufnahme	Frostbeständigkeit	Abriebfestigkeit	Oberflächenhärte
Толщина	Водопоглощаемость	Морозоустойчивость	Устойчивость к истиранию	Твердость поверхности
厚度	吸水性	耐寒性	抗磨损强度	表面硬度
mm	ISO 10545-3 Classe Bla ASTM C 373 (E ≤ 0,5%)	EN 202 ISO 10545-12 ASTM C 1026	EN 154 ISO 10545-7 ASTM C 1027	EN 101 MOHS
12 mm	≤ 0,2%	ingelivo, frostresistent, ingelif, frostbeständig Морозостойкий, 耐寒	PEI IV PEI III Gubbio	MOHS 8 MOHS 7 Gubbio



GL-UGL	GL-UGL		
Resistenza agli agenti chimici	Resistenza allo scivolamento		
Chemical resistance	Anti-slip		
Résistance chimique	Anti-glissant		
Chemische beständigkeit	Rutschhemmend		
Химическая стойкость	Сопротивление скольжению		
化学反应物抗性	抗打滑性		
ISO 10545-13 ASTM C 650	DIN 51130 R	Coefficiente d'attrito BCR TORTUS	ASTM C 1028
TEST EN 122	9÷10	DRY > 0,50 WET > 0,50	DRY > 0,60 WET > 0,60

Si raccomanda la posa in opera con giunto di fuga di dimensione non inferiore a 2 mm. / In the laying operations it's recommended a joint not lower than 2 mm. / Nous recommandons la pose avec des jointures de dimension non inférieure à 2 mm. / Bei Verlegung nicht mit einer Fugenbreite von weniger als 2 mm arbeiten. / При укладке плитки рекомендуется оставлять зазор между плитками не меньше 2 мм. / 建议贴砖时在接合处留下不少于2mm的缝隙。