

MARMOL
MARBLE

BEVERLY

60 x 60 cm · 24" x 24"

GLOSSY FINISH · ACABADO BRILLO · PORCELAIN TILES



Porcelain Tiles
Porcelánico



Floor Tile
Pavimento



Acabado Brillo
Glossy finish



BEVERLY CREAM

60 x 60 CM
PEI V · C0 / B1b
MOHS 5

GT6A



BEVERLY GREY

60 x 60 CM
PEI V · C0 / B1b
MOHS 5

GT6A

VARIACIÓN GRÁFICA / GRAPHIC VARIATION



RODAPIÉ / SKIRTING / PLINTHE

10 x 60 cm · D45



PACKING	BOXES PALLET	SQM BOX	SQM PALLET	KGS PIECE	KGS BOX	KGS PALLET	PIECES BOX	PALLETS CONTAINER	SQM CONTAINER	WEIGHT CONTAINER	THICKNESS	ABSORPTION
60 x 60 CM	30	1,44	43,20	8,000	32,17	980	4	26	1.123,20	25.475	1,00	E<0,5



MERCHANDISING

The image displays a vertical merchandising panel for the 'BEVERLY CASSANDRA' product line. On the left side, there are three large, vertically stacked color swatches: a white surface with prominent gold and brown veins, a solid light orange surface, and a solid light purple surface. The right side of the panel is a dark-themed information section. At the top, it features the 'DIALOGUES DG' logo. Below the logo is a photograph of a modern interior space with a marble floor and contemporary furniture. The product name 'BEVERLY CASSANDRA' is printed in a decorative font. The section is divided into two main product descriptions. The first, 'CASSANDRA BEVERLY 60 x 90 CM GLOSSY FINISH', includes a small image of the product, a 'POPULAR TON' swatch, and a grid of color options. The second, 'BEVERLY BEVERLY 60 x 90 CM GLOSSY FINISH', also includes a small image, a 'POPULAR TON' swatch, and a grid of color options. At the bottom of the panel, there are two more photographs of interior spaces and the website address 'WWW.DIALOGUES.COM'.

D16_039 · PANEL BEVERLY CASSANDRA

CARACTERÍSTICAS TÉCNICAS GRES PORCELÁNICO

TECHNICAL FEATURES PORCELAIN TILES · CARACTÉRISTIQUES TECHNIQUES GRÈS CÉRAMÉ

	NORMAS DE ENSAYO STANDARD NORMES D'ESSAI	VALORES DUALGRES DUALGRES STANDARD VALEURS DUALGRES	
Características dimensionales <i>Dimensional features</i> <i>Caractéristiques dimensionnelles</i>	ISO 10545-2	Cumple la norma <i>Conforms to standard</i> <i>Satisfait à la norme</i>	
Absorción del agua <i>Water absorption</i> <i>Absorption d'eau</i>	ISO 10545-3	0.5 < Eb < 3%	
Resistencia a la flexión · Fuerza de la rotura <i>Modulus of rupture · Breaking strength</i> <i>Résistance à la flexion · Force de rupture</i>	ISO 10545-4	> 30 N/mm ² >1100N	
Resistencia a la abrasión superficial de baldosas esmaltadas para suelos	ISO 10545-7	Indicado por el fabricante	
Dilatación térmica lineal <i>Linear thermal expansion</i> <i>Dilatation thermique linéaire</i>	ISO 10545-8	Método de ensayo disponible <i>Test method available</i> <i>Méthode d'essai disponible</i>	
	NORMAS DE ENSAYO STANDARD NORMES D'ESSAI	VALORES DUALGRES DUALGRES STANDARD VALEURS DUALGRES	
Resistencia al choque térmico <i>Thermal shock resistance</i> <i>Résistance au choc thermique</i>	ISO 10545-9	Resiste <i>Resists</i> <i>Résiste</i>	
Resistencia a la helada <i>Frost resistance</i> <i>Résistance au gel</i>	ISO 10545-12	Resiste <i>Resists</i> <i>Résiste</i>	
Resistencia química <i>Chemical resistance</i> <i>Résistance chimique</i>	Ácidos y bases <i>Acids and bases</i> <i>Acides et bases</i> Productos de limpieza y reactivos a piscinas <i>Cleaning products and pool reactive agents</i> <i>Produits de nettoyage et réactifs de piscines</i>	ISO 10545-13	Cumple la norma <i>Conforms to standard</i> <i>Satisfait à la norme</i> Clase UA <i>Class UA</i> <i>Class UA</i>
Resistencia a las manchas <i>Stain resistance</i> <i>Résistance aux taches</i>	ISO 10545-14	Cumple la norma <i>Conforms to standard</i> <i>Satisfait à la norme</i>	
Resistencia al deslizamiento <i>Slip resistance</i> <i>Résistance au glissement</i>	DIN 51130 UNE-ENV 12633 ASTM C 1028	Según Modelos <i>According to models</i> <i>Selon modèles</i>	



Tel: (+34) 964 77 11 66 / Fax: (+34) 964 77 12 50

web: www.dualgres.com

email: export@dualgres.com

Ctra. de Viver al Puerto de Burriana, km 56,9
ONDA (CASTELLÓN) · SPAIN