

MARMOL  
MARBLE

# CASSANDRA

60 x 60 cm · 24" x 24"

GLOSSY FINISH · ACABADO BRILLO · PORCELAIN TILES



Porcelain Tiles  
Porcelánico



Floor Tile  
Pavimento



Acabado Brillo  
Glossy finish



## CASSANDRA

60 x 60 CM  
PEI IV · C0 / B1b  
MOHS 5

GT6A



RODAPIÉ / SKIRTING / PLINTHE

10 x 60 cm · D45

## VARIACIÓN GRÁFICA / GRAPHIC VARIATION



PACKING	BOXES PALLET	SQM BOX	SQM PALLET	KGS PIECE	KGS BOX	KGS PALLET	PIECES BOX	PALLETS CONTAINER	SQM CONTAINER	WEIGHT CONTAINER	THICKNESS	ABSORPTION
60 x 60 CM	30	1,44	43,20	8,000	32,17	980	4	26	1.123,20	25.475	1,00	E<0,5



# MERCHANDISING

The image displays a vertical merchandising panel for 'BEVERLY CASSANDRA'. On the left side, there are three large, vertically stacked color swatches: a white surface with gold and brown veins, a light orange surface, and a light purple surface. The right side of the panel is a black vertical strip containing the following elements from top to bottom:

- DIGITALS DG** logo.
- A photograph of a modern interior space with a marble floor and contemporary furniture.
- The product name **BEVERLY CASSANDRA** in a decorative font.
- Technical specifications: **CASEWORK SERIES: 60 x 90 CM GLOSSY FINISH** and **POPULAR TON**. It includes a small image of a panel and a list of color options.
- Technical specifications: **BEVERLY SERIES: 60 x 90 CM GLOSSY FINISH** and **POPULAR TON**. It includes two small images of panels and a list of color options.
- Two photographs of a kitchen or office area featuring the product panels.
- The website [WWW.DIGITALS.COM](http://WWW.DIGITALS.COM) and social media icons.

D16\_039 · PANEL BEVERLY CASSANDRA

# CARACTERÍSTICAS TÉCNICAS GRES PORCELÁNICO

TECHNICAL FEATURES PORCELAIN TILES · CARACTÉRISTIQUES TECHNIQUES GRÈS CÉRAMÉ

		NORMAS DE ENSAYO STANDARD NORMES D'ESSAI	VALORES DUALGRES DUALGRES STANDARD VALEURS DUALGRES
Características dimensionales <i>Dimensional features</i> <i>Caractéristiques dimensionnelles</i>		ISO 10545-2	Cumple la norma <i>Conforms to standard</i> <i>Satisfait à la norme</i>
Absorción del agua <i>Water absorption</i> <i>Absorption d'eau</i>		ISO 10545-3	0.5 < Eb < 3%
Resistencia a la flexión · Fuerza de la rotura <i>Modulus of rupture · Breaking strength</i> <i>Résistance à la flexion · Force de rupture</i>		ISO 10545-4	> 30 N/mm <sup>2</sup> >1100N
Resistencia a la abrasión superficial de baldosas esmaltadas para suelos		ISO 10545-7	Indicado por el fabricante
Dilatación térmica lineal <i>Linear thermal expansion</i> <i>Dilatation thermique linéaire</i>		ISO 10545-8	Método de ensayo disponible <i>Test method available</i> <i>Méthode d'essai disponible</i>
		NORMAS DE ENSAYO STANDARD NORMES D'ESSAI	VALORES DUALGRES DUALGRES STANDARD VALEURS DUALGRES
Resistencia al choque térmico <i>Thermal shock resistance</i> <i>Résistance au choc thermique</i>		ISO 10545-9	Resiste <i>Resists</i> <i>Résiste</i>
Resistencia a la helada <i>Frost resistance</i> <i>Résistance au gel</i>		ISO 10545-12	Resiste <i>Resists</i> <i>Résiste</i>
Resistencia química <i>Chemical resistance</i> <i>Résistance chimique</i>	Ácidos y bases <i>Acids and bases</i> <i>Acides et bases</i> Productos de limpieza y reactivos a piscinas <i>Cleaning products and pool reactive agents</i> <i>Produits de nettoyage et réactifs de piscines</i>	ISO 10545-13	Cumple la norma <i>Conforms to standard</i> <i>Satisfait à la norme</i> Clase UA <i>Class UA</i> <i>Class UA</i>
Resistencia a las manchas <i>Stain resistance</i> <i>Résistance aux taches</i>		ISO 10545-14	Cumple la norma <i>Conforms to standard</i> <i>Satisfait à la norme</i>
Resistencia al deslizamiento <i>Slip resistance</i> <i>Résistance au glissement</i>		DIN 51130 UNE-ENV 12633 ASTM C 1028	Según Modelos <i>According to models</i> <i>Selon modèles</i>



Tel: (+34) 964 77 11 66 / Fax: (+34) 964 77 12 50

web: [www.dualgres.com](http://www.dualgres.com)

email: [export@dualgres.com](mailto:export@dualgres.com)

Ctra. de Viver al Puerto de Burriana, km 56,9  
ONDA ( CASTELLÓN ) · SPAIN