



DINAMICO™

COLORBODY™ PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC | TRUEDGE™ | REVEAL IMAGING®

RAGNO®

ARTFULLY REIMAGINED™



COLOR NAME



DINAMICO™

The look of travertine in elegant, unexpected colors, Dinamico will inspire you to design outside the box. The large-format sizes expand the space in either 12x24 or 18x36 with a coordinating 1x4 mosaic. Linear influences enhance the travertine stone look whose details are enriched by a glossy application to create dynamic light reflections. Available in White, Grey, and Beige.





COLOR NAME

COLORBODY™ PORCELAIN FLOOR TILE



DN30 White



DN31 Greige



DN32 Silver

GLAZED CERAMIC 1 x 3 HERRINGBONE MOSAIC
9 x 12 SHEET



DN30 White



DN31 Greige



DN32 Silver

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	18 x 36 Floor Tile	(17-9/16" x 35-1/4") (44.65 cm x 89.50 cm)	3/8"	12.90	3
	12 x 24 Floor Tile	(11-9/16" x 23-7/16") (29.40 cm x 59.50 cm)	5/16"	16.83	9
	1 x 3 Herringbone Mosaic (Dot-Mounted)	(9" x 12" Sheet) (22.86 cm x 30.48 cm Sheet)	1/4"	6.00	10

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	•
Wet & Level – Interior Floor	≥ 0.42	•
Shower Floors (Residential or Light Commercial)	≥ 0.42	•*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	•
Countertops	N/A	•
Pool Linings	N/A	•*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit ragnousa.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only



Floor Tile



Wall Tile



TruEdge™




Reveal Imaging®


Pre-Consumer
Recycled ContentPost-Consumer
Recycled Content

All or select items within this series meet the requirements for these qualifications. For more information visit ragnousa.com.

TRIM

DESCRIPTION	NUMBER	SIZE	SHAPE
Floor Bullnose	P-43F9	3 x 24	

INSTALLATION

GROUT JOINT RECOMMENDATION	SHADE VARIATION
Floor: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%) Mosaic: 1/8"	 High Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	N/A	N/A

For additional information on test results, visit us at: ragnousa.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: ragnousa.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to ragnousa.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

PHOTOGRAPHY INDEX

Cover
Collection Name™ in Color name - structure or finish on area

Page 2
Collection Name™ in Color name - structure or finish on area

Page 4
Collection Name™ in Color name - structure or finish on area