


FS Alora

Single fired floor tiles



FS ALORA

FS ALORA



45 * 45 * 1,05 cm | 17 3/4 * 17 3/4 * 7/16 "

NO RECTIFIED	NATURAL PEI CODE BN14
FS ALORA	19277

PIEZA COMPLEMENTARIA | COMPLEMENTARY PIECE
*Pedido mínimo 10 unidades | Minimum order 10 items

Rodapie - Skirting

R.

8 * 45 cm | 3 1/8 * 17 3/4" P8

CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO | ANTI-SLIP CHARACTERISTICS

Ensayo Essay	Características Features	Resultado Result
DIN 51130	Ángulo crítico (Pies calzados) Critical angle (footwear)	R9
DIN 51097	Ángulo crítico (Pies descalzos) Critical angle (Wet loaded barefoot)	-
BS-7976-2	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	+36Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	Class 1
ANSI A.1371:2012	Coefficiente de Fricción Dinámico Dynamic Coefficient of Friction (DCOF)	>0,42
ISO 10545-7	Resistencia a la Abrasión Superficial/ Resistance to Surface Abrasion	PEI 4

CARACTERÍSTICAS TÉCNICAS | TECHNICAL CHARACTERISTICS

joint 1,5 mm	versatile	matt	diferent shades
shade variation V3	various graphics	various moulds	

EMBALAJE | PACKING

Formato Sizes	Cajas Boxes			Pallet			Cont./20' 21500 kg.	Cont./20' 24000 kg.	
	Piezas	m ² / sq.m	kg	Cajas	m ² / sq.m	kg	Tamaño cm aprox.	m ² / sq.m	m ² / sq.m
45 * 45 * 1,05	5	1,00	23,14	66	66,00	1552,24	102 * 80 * 105	914,16	1020,46
inch	Units	ft²	lb	Boxes	ft²	lb	Sizes inch approx.	ft²	ft²
17 3/4 * 17 3/4 * 7/16	5	10,76	50,91	66	710,42	3414,93	40 3/16 * 31 1/2 * 41 5/16	9839,96	10984,14