

# FS Melvin

Porcelain tiles



FS MELVIN WHITE



7,4 \* 67,5 \* 1,05 cm | 2 15/16 \* 29 9/16 \* 7/16"

NO RECTIFIED	NATURAL PRICE CODE BN73
WHITE	20033
COLOR	20032

## CARACTERÍSTICAS TÉCNICAS | TECHNICAL CHARACTERISTICS

joint 4 mm	frost proof *	versatile L	matt ■
diferent shades ■	shade variation V	various graphics L	various moulds =

## CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO | ANTI-SLIP CHARACTERISTICS

Ensayo   Essay	Características   Features	Resultado   Result
DIN 51130	Ángulo crítico (Pies calzados)   Critical angle (footwear)	R9
DIN 51097	Ángulo crítico (Pies descalzos)   Critical angle (Wet loaded barefoot)	-
BS-7976-2	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test)	+25-30Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test)	Class 1
ANSI A.1371:2012	Coefficiente de Fricción Dinámico   Dynamic Coefficient of Friction (DCOF)	-
ISO 10545-7	Resistencia a la Abrasión Superficial/ Resistance to Surface Abrasion	COLOR_PEI 3 WHITE_PEI 4

## EMBALAJE | PACKING

Formato   Sizes	Cajas   Boxes			Pallet				Cont./20'	Cont./20'
	Piezas	m <sup>2</sup> / sq.m	kg	Cajas	m <sup>2</sup> / sq.m	kg	Tamaño cm aprox.	m <sup>2</sup> / sq.m	m <sup>2</sup> / sq.m
7,4 * 67,5 * 1,05	15	0,75	17,25	63	47,20	1111,75	120 * 80 * 83	912,85	1018,99
inch	Units	ft <sup>2</sup>	lb	Boxes	ft <sup>2</sup>	lb	Sizes inch approx.	ft <sup>2</sup>	ft <sup>2</sup>
2 15/16 * 29 9/16 * 7/16	15	8,06	37,95	63	508,09	2445,85	47 1/4 * 31 1/2 * 32 11/16	9825,81	10968,34