


## LUX 2.0

+ REDEFINING MARBLED BEAUTY +





### LUX 2.0

+ REDEFINING MARBLED BEAUTY +

An ode to timeless style, Lux 2.0 – the latest digital glazed polished tile collection by tiling expert Niro Ceramic – takes cues from natural marble itself. After all, the beautiful veined stone has long been associated with a poised elegance and class.

In a similar fashion, Lux 2.0 aspires to conjure sophistication in any spaces it graces. Thanks to advanced decoration technology, all the beautiful movement in the marble is skillfully recreated upon the tile surface. With no marbled effect appearing the same, it further enhances the authenticity of the design.

Lux 2.0 users can expect two options of finishes, made suitable for different areas. The digital glazed polished tiles are a smart choice for the likes of living room and bedroom, as these spots tend to experience softer footfall. The soft polished version, on the other hand, is intended to withstand regular foot traffic in places like kitchen, balcony and terraces.

Either way, the tile collection guarantees to be a worthwhile addition to your home. Because your home is your personal sanctuary, it deserves a treatment as beautiful as Lux 2.0.



#### **POLISHED**

#### APPLICATION


Residential light traffic area for internal and very suitable for wall application.

#### SOFT POLISHED



#### APPLICATION

Residential high traffic area for internal and very suitable for wall application.







#### **GXP19 ARIA**

80x80cm . 60x60cm

#### POLISHED . MATT\* \*matt only for size 60x60cm














#### **GXP30 DOLCE**

 $80x80cm \cdot 60x60cm$ 

#### POLISHED . MATT\* \*matt only for size 60x60cm











#### **GXP76 DIVA**

80x80cm . 60x60cm

#### **POLISHED**











**GXP31 OPERA** 

80x80cm

SOFT POLISHED



# PERA





**GXP34 CELESTA** 

80x80cm

SOFT POLISHED









**GXP47 TUBA** 

80x80cm

SOFT POLISHED



TUBA





**GXP58 FARSA** 

80x80cm

SOFT POLISHED








# R E D E F I N I N G M A R B L E D B E A U T Y

V3

#### **POLISHED**



GXP19 ARIA 80x80cm - polished 60x60cm - polished . matt



GXP27 TUTTI
80x80cm
polished



GXP30 DOLCE 80x80cm - polished 60x60cm - polished . matt



V3

GXP39 VIOLA
60x60cm
polished




GXP76 DIVA

80x80cm . 60x60cm

polished

#### **SOFT POLISHED**



GXP31 OPERA
80x80cm
soft polished



GXP34 CELESTA 80x80cm soft polished



GXP47 TUBA 80x80cm soft polished



GXP58 FARSA V3 80x80cm soft polished



#### TECHNICAL SPECIFICATIONS

DESCRIPTION	STANDARD TEST	MEASUREMENT UNIT	ISO STANDARD REQUIREMENT	NIRO GRANITE
Length & Width	ISO 10545 -2	mm	±0.6% Max	±0.30% Max
Thickness	ISO 10545 -2	mm	±5.0% Max	±5.0% Max
Sides Straightness	ISO 10545 -2	mm	±0.5% Max	±0.25% Max
Rectangularity	ISO 10545 -2	mm	±0.5% Max	±0.25% Max
Flatness: a) Centre Curvature	ISO 10545 -2	mm	±0.5% Max	±0.20% Max / Max 2.0mm
b) Edge Curvature	ISO 10545 -2	mm	±0.5% Max	±0.20% Max / Max 2.0mm
c) Warpage	ISO 10545 -2	mm	±0.5% Max	±0.20% Max / Max 2.0mm
Surface Quality	ISO 10545 -2	One Major Area of Tiles	≥ 95% free from visible defect	Comply
Water Absorption	ISO 10545 -3	Mass	≤0.5%	≤0.20%
Breaking Strength	ISO 10545 -4	N	≥ 1300 N	≥ 1300 N
Modulus of Rupture	ISO 10545 -4	N/mm²	≥ 35 N/mm² Individual ≥ 32 N/mm²	≥ 35 N/mm² Individual ≥ 32 N/mm²
Abrasion Resistance Surfaces Abrasion for glazed tiles	ISO 10545 -7	Visual Check	Manuf. to state abrasion class, cycle and passed	≥ PEI 3 ( Dependent on product type )*
Crazing Test (glazed tiles)	ISO 10545 -11	Visual Check	No Sign of Crazing	No Sign of Crazing
Frost Resistance	ISO 10545 -12	Visual Check	Required	No Visible Crack
Chemical Resistance a) Low concentrations	ISO 10545 -13	Visual Check	Manuf. To State	Class A Class B (For Polished Tile)
<ul> <li>b) Household chemicals and swimming pool salts</li> </ul>	ISO 10545 -13	Visual Check	≥ Class B	Class A Class B (For Polished Tile)
Stain Resistance				
For glazed tiles	ISO 10545 -14	Visual Check	≥ Class 3	≥ Class 3
Slip Resistance (Excluding Polished, Lappato and Matt Satin finishing)	AS/NZS 4586 App. A	PO to P5	Manuf. to State	Wet Pendulum: Matt: P2

 $\label{thm:continuous} The \ technical \ specifications \ is \ only \ for \ rectified \ tiles. \ \star \ Refer \ to \ test \ report \ for \ specific \ test \ result.$ 

Each different tiles series are produced to meet different performance requirements. For specific product technical performance, please request from Niro Granite sales team or their agent or distributor.



Colour Variations: Since the colour reproduction in this printed piece will vary from the actual tile colours, final selection should be made from tile samples. Colour, shade and glaze variations may exist due to the inherent characteristics of porcelain tile.

Due to the low porosity of porcelain tiles, an Improved High Performance Cementitious adhesive in accordance to BS EN 12004 & ISO 13007-1 is highly recommended for proper installation. Products that meet this standard are available amongst leading adhesive manufacturers. Please seek expert advice from adhesive manufacturers for proper selection and application.

#### SHADE VARIATION:





#### MODERATELY NOTICEABLE FROM TILE TO TILE

The range of colours and tones within the same shade is moderately noticeable from tile to tile. Clearly distinguishable differences in design or pattern.



# LUX 2.0

+ REDEFINING MARBLED BEAUTY +

#### NIRO CERAMIC GROUP

Lot 2, Persiaran Sultan, Seksyen 15, 40200 Shah Alam, Selangor, Malaysia. T +603 5033 9333 F +603 5033 9323



www.nirogranite.com

facebook /nirogranite.niroceramicgroup /CreativeLabbyNiroGranite instagram
/Niro\_Granite
/creativelab\_my

youtube /Niro Granite

