



# FS Marrakech

Single fired floor tiles



FS MARRAKECH | FS MARRAKECH GREY FS OMEYA GREY, BLACK; WHITE


NEW



FS MARRAKECH Grey



FS MARRAKECH blue



6 patterns

45\*45\*1,05 cm | 17 3/4" \* 17 3/4" \* 7/16"

	<b>NATURAL</b> PRICE CODE BN14
<b>GREY</b>	21937
<b>BLUE</b>	21936







### CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO | ANTI-SLIP CHARACTERISTICS

Ensayo   Essay	Características   Features	Resultado   Result
DIN 51130	Ángulo crítico (Pies calzados)   Critical angle (footwear)	R9
DIN 51097	Ángulo crítico (Pies descalzos)   Critical angle (Wet loaded barefoot)	—
BS-7976-2	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test)	+36 Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test)	Class 1
ANSI A.1371:2012	Coefficiente de Fricción Dinámico   Dynamic Coefficient of Friction	—
ISO 10545-7	Resistencia a la Abrasión Superficial/Resistance to Surface Abrasion	PEI 4

### APLICACIONES | APPLICATIONS

Área   Area	Revestimiento   Wall	Pavimento   Floor
Interior   Internal	✓	✓
Exterior   External	-	-
Comercial   Commercial	-	-
Ducha   Shower	-	-

### CARACTERÍSTICAS TÉCNICAS | TECHNICAL CHARACTERISTICS

joint	versatile	matt
		
diferent shades	shade variation	various graphics
		

### EMBALAJE | PACKING

Formato   Sizes	Cajas   Boxes			Pallet			Cont./20'		
	Piezas	m <sup>2</sup> / sq.m	kg	Cajas	m <sup>2</sup> / sq.m	kg	Tamaño cm aprox.	m <sup>2</sup> / sq.m	m <sup>2</sup> / sq.m
cm									
45 * 45 * 1,95	5	1	23,14	66	66,83	1552,2	120 * 80 * 105	925,59	1033,22
inch									
17 3/4 * 17 3/4 * 3/4	5	10,9	50,9	66	719,3	3414,9	47 1/2 * 31 1/2 * 41 5/16	9962,96	11121,44