

CEMENTO  
CEMENT

# URANO

45 x 45 cm · 18" x 18"

MATT FINISH · FROST PROOF / ACABADO MATE · ANTI-HIELO  
RED BODY PORCELAIN



Porcelain Tiles  
Porcelánico



Paivmento  
Floor Tile



Mate  
Matt



Relieve  
Relief



Anti-dslizante  
Anti-slip



DK Urano Cotto

GT3A

45 x 45 CM  
C3(R11)

DIFFERENT DESIGNS IN EACH BOX



DK Urano Cement

GT3A

45 x 45 CM  
C3(R11)



PACKING	BOXES PALLET	SQM BOX	SQM PALLET	KGS PIECE	KGS BOX	KGS PALLET	PIECES BOX	PALLETS CONTAINER	SQM CONTAINER	WEIGHT CONTAINER	THICKNESS	ABSORPTION
DK- 45 x 45 CM	44	1,42	62,48	3,880	27,26	1.214	7	20	1.249,60	24.283	0,90	E<0,5




# MERCHANDISING



BEL17\_002 · PANEL URANO

# TECHNICAL SHEET CARACTERÍSTICAS TÉCNICAS

UNE-EN.14411:2016 Norma/Norm		Gres porcelánico Porcelain Tiles	
UNE-EN-ISO 10545		ANEXO / ANNEX G	ANEXO / ANNEX G
		GRUPO / GROUP Bla	GRUPO / GROUP Bla
		N≥15cm	N≥15cm
Absorción de agua /Water absorption	E≤0,50%	E≤0,30%	
Fuerza de Rotura en N /Breaking Strength, in N	≥ 1300N	≥ 2000N	
Resistencia a la Flexión N/mm <sub>2</sub> /Modulus of rupture, in N/mm <sub>2</sub>	Media / Average ≥ 35	Media/Average ≥ 43	

	TEST METHOD	STANDARD	
	<b>RESISTENCIA AL DESLIZAMIENTO</b> /SLIP RESISTANCE	UNE-ENVE-12633	CTE
BS 7976-2: 2002		PTV	<b>LOW (40)</b>
AS/NZS 4586: 2013		Pendulum SRV	<b>P3</b>
DIN 51130: 2014		Inclined Plane	<b>R10</b>
ANSI A137.1: 2012 (DCOF)		≥ 0,42W	<b>0,72W</b>



## CONTACT US:

Ctra. de Viver al Puerto de Burriana, km 56,9  
ONDA ( CASTELLÓN ) · SPAIN

Tel: (+34) 964 77 11 66

[www.dualgres.com](http://www.dualgres.com) [export@dualgres.com](mailto:export@dualgres.com)

